



ELECTRIC DRIVES
FOR EVERY DEMAND



Brake motors

Designed for IE1, IE2 and IE3

www.vem-group.com





Brake motors

Drives for hoists, cranes, winches, conveyors or machine tools

Stopping straight off

For many applications, it is imperative to be able to stop the drives quickly and reliably. For lifts, hoists, cranes, winches, conveyors and machine tools, brake motors from VEM are an ideal and secure choice.

- › They comprise a VEM three-phase squirrel-cage motor and a mounted brake.
- › The mounted brake can be supplied by a number of different manufacturers.
- › The brakes are designed as twin-disc spring-operated brakes and function on the fail-safe principle.
- › The brake systems can be supplied as a compact unit ready for connection and assembly.
- › The most varied brake torques and designs can be implemented upon request by the customer.
- › They are available in all efficiency classes.

Reliable stopping and starting

Brake motors always apply a holding torque in the no-voltage state. Compression springs apply a force to the axially free armature disc, which builds up a braking torque via friction linings. The brake torque is transmitted to the shaft via the keyed joint to the lining carrier or a toothed driver hub. When a voltage is applied to the brake coil, the armature disc is lifted, releasing the brake linings and permitting the motor to start up.

Series	B21R, IE1 -B21R, IE2-BE1R and IE3-B41R, mounting dimensions and output correlation acc. to EN 50347, B20R, B22R, Transnorm version
Sizes	63 to 355
Output range	0.18 – 500 kW
Efficiency class	without, IE1, IE2 and IE3 according to IEC/EN 60034-30-1 in the power range 0.75...275 kW, 2-, 4-, 6- and 8-pole
Types of protection	IP 55 acc. to IEC/EN 60034-5, higher degrees of protection as an option
Types of construction	IM B3, IM B35, IM B5 and derived types of construction acc. to IEC/EN 60034-7
Cooling method	IC 411 acc. to IEC/EN 60034-6
Brakes	Double-face spring-pressure brakes
Brake manufacturer/ type	Stromag BZFM, 4BZFM, BZFA, NFE Intorq BFK 458 PINTSCH BAMAG KFB, SFB Mayr./800.410.3 KEB../08.2.0



Brake motors are used wherever it is imperative to be able to stop the drives quickly and reliably.

Size	Rated output P [kW]				Size	Rated output P [kW]			
	2-pole	4-pole	6-pole	8-pole		2-pole	4-pole	6-pole	8-pole
rpm	3000	1500	1000	750	rpm	3000	1500	1000	750
63 K	0.18	0.12	0.09	-	180 M	22	19	-	-
63 G	0.25	0.18	0.12	-	180 L	-	22	15	11.0
71 K	0.37	0.25	0.18	0.09	200 L	30	30	19	15.0
71 G	0.55	0.37	0.25	0.12	200 LX	37	-	22	-
80 K	0.75	0.55	0.37	0.18	225 S	-	37	-	18.5
80 G	1.1	0.8	0.6	0.25	225 M	45	45	30	22
90 S	1.5	1.1	0.8	0.37	250 M	55	55	37	30
90 L	2.2	1.5	1.1	0.55	280 S	75	75	45	37
100 L	3.0	2.2	1.5	0.75	280 M	90	90	55	45
100 LX	-	3.0	-	1.1	315 S	110	110	75	55
112 M	4.0	4.0	2.2	1.5	315 M	132	132	90	75
112 MX	-	-	-	-	315 MX	160	160	110	90
132 S.T	5.5	5.5	3.0	2.2	315 MY	200	200	132	110
132 SX.T	7.5	-	-	-	315 L	250	250	160	132
132 S	5.5	5.5	3.0	2.2	315 LX	315	315	200	160
132 SX	7.5	-	-	-	355 M	355	355	250	200
132 M	-	7.5	4.0	3.0	355 MX	400	400	315	250
132 MX	-	-	5.5	-	355 LY	450	450	355	280
160 M	11.0	11.0	7.5	4.0	355 L	500	500	-	-
160 MX	15.0	-	-	5.5					

Please refer to our catalogues for technical details. The catalogues are available in printed or in digital version on DVD. They are also available in the internet.



VEM Holding GmbH

Pirnaer Landstraße 176
D-01257 Dresden

Phone: +49 351 208-0
Fax: +49 351 208-1028

VEM Sales

Low voltage

Phone: +49 3943 68-0
E-Mail: motors@vem-group.com

High voltage

Phone: +49 351 208-0
E-Mail: sachsenwerk@vem-group.com

Drive systems

Phone: +49 30 9861-2104
E-Mail: transresch@vem-group.com



For detailed information
please visit our website.